

ATR2700ES

RACK CONVEYOR DISHWASHER LEFT-HAND SIDE ENTRY 2700 PLATES PER HOUR



PRODUCT DESCRIPTION

ATR2700 ES: Rack conveyor dishwasher with **electric feeding** and **left-hand side rack entry**

Stainless steel structure 18/10 AISI 304. Sturdy counter-balanced door.

Wash tank with rounded edges and inclination, thus ensuring the complete drainage of dirty water.

Stainless steel upper and lower wash and rinse arms that can be easily taken out for cleaning.

A washing area and a double rinsing area.

Three-speed rack movement with a washing capacity of 80 racks/hour (speed 1) or 115 racks/hour (speed 2) or 150 racks/hour (speed 3).

High capacity **double-boiler system**.

Double stainless steel surface filters in the tank with an easily removable basket for collecting solid waste.

Compact geared motor with integrated clutch.

Ergonomic control panel in order to make the temperatures and the different working steps easily recognisable.

Possibility to program the water temperature in each wash tank and to set the rinsing temperature.

Equipped with non-return valve avoiding dirty water to flow back into the main water system (DVGW approved).

Standard equipped with a stainless steel connection for detergent dispenser in each wash tank. Prearranged for detergent dispenser and rinse aid dispenser.

Wide range of accessories and options available **on demand**: drying tunnel, steam condenser with or without heat recovery, steam exhauster, rinse aid dispenser and detergent dispenser.

Entry and exit tables available **on demand**.

Standard equipped with three racks for plates, a rack for tableware and rack for glasses.

IPX5 Protection

Option: connection to cold water for a total power of **36,3 kW**.



TECHNICAL SPECIFICATIONS

Width: 1570 mm
Depth: 800 mm
Height: 1580 mm
Volume: 1.99 m³
Rack dimensions: 500x500 mm
Useful height: 410
Electrical power: 27.30 kW
Electric power: 230 V / 3 - 400 V / 3+N/ 50-60 Hz
Racks/Hour: 80-115-150
Dishes/Hour: 1440-2070-2700

