

# B50

## HOOD TYPE DISHWASHER



### PRODUCT DESCRIPTION

Stainless steel structure and tank AISI 304.  
Upper and lower rotating wash and rinse arms.  
Stainless steel pump intake filter.

**Electro-mechanic functioning.**

**Two working cycles:** 60 seconds and 150 seconds.

Stainless steel heating elements, resistant to corrosion and limescale.

Suitable for line or corner installations. Height-adjustable legs.

Hood lifting thanks to springs.

The washing cycle starts only when the hood is completely closed.

The appliance stops working if the hood is lifted by chance.

**Standard equipped** with a built-in rinse aid dispenser for the best drying results.

**Standard equipped** with a built-in connection for detergent dispenser.

As option, stainless steel surface filter available **on demand**.

**Standard equipped** with a basket for plates and a basket for cups.



## TECHNICAL SPECIFICATIONS

**Width:** 760 mm

**Depth:** 760 mm

**Height:** 1420 mm

**Volume:** 0.83 m<sup>3</sup>

**Rack dimensions:** 500x500 mm

**Useful height:** 395 mm

**Working cycles:** 60-150 sec

**Electrical power:** 6.80 kW

**Electric power:** 230 V / 1 - 230 V / 3 - 400 V / 3+N/ 50-60 Hz

**Dishes/Hour:** 1080-432

