



No.145, 11th Industry Rd. Ta-Li City,
Taichung Hsien 412 Taiwan
Phone:886-4-2491-7585
E-Mail:spar@tcts.seed.net.tw

SP-5MX Mixer

Specifications

● Motor <<<<<

1/3 HP grease packed ball bearing, air-cooled,
110/60/1 (50Hz available)

● Controls <<<<<

Spar Mixer controls are front-mounted to give easy access in cramped kitchen environments. The following controls are standard on all Spar Mixers: separate start and emergency stop buttons so operators can shut down the mixer immediately in an emergency situation, and thermal overload protection

● Cord and Plug <<<<<

6 ft. flexible three wire cord and ground prong.

● Transmission <<<<<

Heat-treated, hardened alloy, precision milled gears operate with planetary action. Gears are packed in a long-lasting, high pressure grease. Planetary gears are driven by direct linkage to the motor drive shaft. This design yields high-torque mixing power.

● Speeds <<<<<

Speed	Agitator rpm	Hub rpm's
Low Speed	106	59
Intermediate Speed	196	110
High Speed	358	201

● Bowls and Agitators <<<<<

Standard equipment includes a 10Qt. high quality stainless steel bowl, dough hook, flat beater, and whip. A sturdy hand lever on the body column raises and lowers the bowl as well as locking in place at the top and bottom positions.

● Attachments <<<<<

Standard is the No. 12 hub for powering a standard size vegetable slicer/cheese shredder and a standard size meat mincer/grinder.



SP-5MX Mixer

● Finish <<<<<

Top (transmission cover): metallic
bronze epoxy enamel
Bottom:metallic gray epoxy enamel

● Shipping Information <<<<<

N.W. 65kgs
G.W. 90kgs

Carton Size:
Depth x Width x Height
60cm x 52cm x 86cm

Cartons are affixed to an under-sized skid (pallet), the weight and dimensions of this skid are not included above and may vary from shipment to shipment.

SP-5MX <<<<<