



No.147, 11th Industry Rd. Ta-Li City,
Taichung Hsien 412 Taiwan
Phone:886-4-2491-7585
E-Mail:spar@tcts.seed.net.tw

SP-7MX Mixer

Specifications

● Motor <<<<<<
1/2 h.p., grease packed ball bearing, air-cooled,
110/60/1 (50Hz available)

● Controls <<<<<<
The following controls are standard on all Spar
Mixers: separate start and emergency stop buttons so
operators can shut down the mixer immediately in an
emergency situation, and thermal overload protection

● Cord and Plug <<<<<<
6 ft. flexible three wire cord and ground prong.

● Transmission <<<<<<
Heat-treated, hardened alloy, precision milled gears
operate with planetary action. Gears are packed in a
long-lasting, high pressure grease. Planetary gears
are driven by direct linkage to the motor drive shaft.
This design yields high-torque mixing power.

● Speeds: <<<<<<
(Agitator rpm), (Hub rpm's)
1. Low Speed 106, 59
2. Intermediate Speed 196, 110
3. High Speed 358, 201

● Bowls and Agitators <<<<<<
Standard equipment includes a 20Qt. high quality
stainless steel bowl, dough hook, flat beater, and
whip. A sturdy hand lever on the body column raises
and lowers the bowl as well as locking in place at the
top and bottom positions.

● Attachments <<<<<<
Standard is the No. 12 hub for powering a standard
size vegetable slicer/cheese shredder and a standard
size meat mincer/grinder.



SP-7MX Mixer

● Finish <<<<<<
Top (transmission cover): metallic
bronze epoxy enamel
Bottom:metallic gray epoxy enamel

● Shipping Information <<<<<<
N.W. 80kgs
G.W. 100kgs

Carton Size:
Depth x Width x Height
60cm x 58cm x 96cm

Cartons are affixed to an under-
sized skid (pallet), the weight and
diminsions of this skid are not
included above and may vary from
shipment to shipment.shipment to
shipment.

SP-7MX <<<<<<